

CHH H2 S Termite treated LVL & Hyjoist

Carter Holt Harvey LVL Ltd (Trading as Futurebuild LVL)

Chemwatch Hazard Alert Code: 1

Chemwatch: 4729-41

Issue Date: 25/01/2019

Version No: 14.1.1.1

Print Date: 07/07/2019

Safety Data Sheet according to WHS and ADG requirements

L.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	CHH H2 S Termite treated LVL & Hyjoist
Synonyms	Not Available
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Used in residential, commercial, and industrial construction, and/or general purpose building material.
--------------------------	---

Details of the supplier of the safety data sheet

Registered company name	Carter Holt Harvey LVL Ltd (Trading as Futurebuild LVL)
Address	PO Box 425 Box Hill VIC 3128 Australia
Telephone	1800 808 131
Fax	Not Available
Website	fblvl.com.au
Email	info@fblvl.com.au

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification	Not Applicable

Label elements

Hazard pictogram(s)	Not Applicable
---------------------	----------------

SIGNAL WORD **NOT APPLICABLE**

Hazard statement(s)

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Continued...

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available	>90	wood veneer
40798-65-0	<10	<u>phenol/ formaldehyde polymer sodium salt</u>
Not Available		insecticide, as
82657-04-3	<0.015	<u>bifenthrin</u>
Not Available		In use, may generate wood dust softwood
Not Available		THIS REPORT IS FOR TREATED PRODUCT ONLY

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<ul style="list-style-type: none"> ▶ Hazard relates to dust released by sawing, cutting, sanding, trimming or other finishing operations. If this product comes in contact with eyes: <ul style="list-style-type: none"> ▶ Wash out immediately with water. ▶ If irritation continues, seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	Brush off dust. In the event of abrasion or irritation of the skin seek medical attention.
Inhalation	<ul style="list-style-type: none"> ▶ If dust is inhaled, remove from contaminated area. ▶ Encourage patient to blow nose to ensure clear passage of breathing. ▶ If irritation or discomfort persists seek medical attention.
Ingestion	<ul style="list-style-type: none"> ▶ Hazard relates to dust released by sawing, cutting, sanding, trimming or other finishing operations. ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ Water spray or fog.
- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid exposure to excessive heat and fire.
-----------------------------	--

Advice for firefighters

Fire Fighting	Alert Fire Brigade and tell them location and nature of hazard. Use water delivered as a fine spray to control the fire and cool adjacent area. Wear breathing apparatus plus protective gloves. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	Combustible. Will burn if ignited. - Wood products do not normally constitute an explosion hazard. - Mechanical or abrasive activities which produce wood dust, as a by-product, may present a severe explosion hazard if a dust cloud contacts an ignition source. - Hot humid conditions may result in spontaneous combustion of accumulated wood dust. - Partially burned or scorched wood dust can explode if dispersed in air.
HAZCHEM	Not Applicable

CHH H2 S Termite treated LVL & Hyjoist

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Pick up. Refer to major spills.
Major Spills	Pick up. Secure load if safe to do so. Bundle/collect recoverable product.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	Use gloves when handling product to avoid splinters.
Other information	▸ Keep dry

Conditions for safe storage, including any incompatibilities

Suitable container	▸ Generally not applicable.
Storage incompatibility	▸ Keep dry

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
CHH H2 S Termite treated LVL & Hyjoist	Not Available	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
phenol/ formaldehyde polymer sodium salt	Not Available	Not Available
bifenthrin	Not Available	Not Available

MATERIAL DATA

for wood dust softwood: Australia Exposure Standards: ES TWA: 5 mg/m3; STEL: 10 mg/m3; Sensitiser

Exposure controls

Appropriate engineering controls	<p>▸ Hazard relates to dust released by sawing, cutting, sanding, trimming or other finishing operations. Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine</p>
---	---

CHH H2 S Termite treated LVL & Hyjoist


the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Personal protection	
Eye and face protection	When sawing, machining or sanding use - Safety glasses with side shields.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▶ Protective gloves eg. Leather gloves or gloves with Leather facing ▶ Safety footwear
Body protection	See Other protection below
Other protection	<p>No special equipment needed when handling small quantities.</p> <p>OTHERWISE:</p> <ul style="list-style-type: none"> ▶ Overalls. ▶ Barrier cream. ▶ Eyewash unit.

Respiratory protection

- ▶ Avoid generating and breathing dust.
- ▶ Effective dust extraction and good ventilation is required when using cutting, shaping or sanding tools. Wear a disposable dust mask AS/NZS 1715:2009 class P1 or P2 when machining.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Pressed boards ranging in thickness from 30mm to 90mm. These boards are ripped into strips between 35 and 600mm wide to form lineal wood components. Bifenthrin treatment is applied during manufacture and the product is coated yellow for easy identification. THIS CHEMWATCH REPORT IS FOR TREATED PRODUCT ONLY.		
Physical state	Manufactured	Relative density (Water = 1)	0.5-1.0
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	>200

Continued...

CHH H2 S Termite treated LVL & Hyjoist

pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Not normally a hazard due to physical form of product. Generated dust may be discomforting
Ingestion	Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments Ingestion of sawdust may cause nausea, abdominal pain, vomiting or diarrhoea.
Skin Contact	The dust is discomforting and mildly abrasive to the skin and may cause drying of the skin, which may lead to contact dermatitis.
Eye	The dust may produce eye discomfort causing transient smarting, blinking
Chronic	<p>▸ Hazard relates to dust released by sawing, cutting, sanding, trimming or other finishing operations.</p> <p>Common chronic responses to wood dust exposures are dermatitis, simple bronchitis and non asthmatic chronic airflow obstruction. Wood is an organic substrate for growth of micro-organisms and fungal spores, these readily become airborne with wood dust and have caused a variety of respiratory infections Various woods, mainly tropical varieties, are able to induce allergies in joiners, carpenters, cabinet makers and model-makers. Allergies of the immediate type (rhino conjunctivitis, bronchial asthma, urticaria), caused by contact with dusts produced during wood-working and those of a delayed type (contact eczema) caused by both the dust and by direct contact with the solid wood, are seen in an occupational setting. Because of the large number of substances found in wood, only a few low molecular weight allergens have been isolated and identified; these are mostly quinone or flavone derivatives. Many of the constituents of wood may also cause primary irritation. Irritation of the skin, eyes and respiratory passages are often distinguished from allergic responses with difficulty.</p> <p>The use of skin tests with wood dusts to confirm suspected allergy must be viewed as suspect because the high concentration of wood components which are sometimes applied, can actually produce new sensitisation in test subjects. It should also be noted that cross-reactions or reactions to groups of similar substances, in other woods and also in other herbaceous plants can also occur. The substances in wood responsible for respiratory allergies are probably mostly high molecular weight substances. Wood dusts may induce asthmatic reactions of both the immediate and delayed types, and occasionally, both. Positive results in bronchial provocation tests, are often, but not always, associated with positive results in skin tests and IgE induction. Bronchial provocation tests may produce different results dependent on whether they are carried out with coarse or fine dusts or with lyophilised aqueous extracts. Very coarse dust may produce false negatives and very fine dust may produce false positives (irritation). Non-allergenic bronchial and nasal irritation are seen frequently.</p>

CHH H2 S Termite treated LVL & Hyjoist

Certain exotic woods contain alkaloids which may produce headache, anorexia, nausea, bradycardia and dyspnea. Agents used to treat wood (preservatives, fungicides, stains, glues, pore fillers) may themselves be responsible for allergic reaction. Other allergic reactions may be provoked by liverworts ("Frullania dermatitis"), lichens, fungi (e.g. bronchopulmonary aspergillosis), actinomycetes or other plants which grow on wood. Microorganisms and fungal spores, associated with wood, may become airborne and provoke allergic responses. Other chronic responses associated with exposure to wood dusts include conjunctivitis, simple bronchitis and non-asthmatic chronic airflow obstruction.

Epidemiologic studies in furniture workers show an increased risk of lung, tongue, pharynx and nasal cancer (adenocarcinoma). Workers in timber industries, with a history of exposure to wood dust, have shown increased occurrence of lung, liver and vocal cavity cancer. An excess risk of leukaemia amongst mill-wrights probably is associated with various components used in wood preservation. It is now suggested that sinonasal cancers may be caused by both hardwoods and softwoods (1). The causative agent or agents are unknown although certain aldehydes or their quinone oxidation products have been implicated. Exposure standards for the softwoods reflect the apparent low risk for upper respiratory tract involvement among workers in the building industry. A significantly lower exposure standard for hardwoods is based on impaired nasal mucociliary hyperplasia reported to contribute to nasal adenocarcinoma and related hyperplasia in furniture workers. Exposure standards for both hard and softwoods specifically exclude the issue of occupational asthma and related allergic respiratory response associated with exposure to red cedar dusts and similar woods.

|Wood dust may cause skin and respiratory sensitisation.

CHH H2 S Termite treated LVL & Hyjoist	TOXICITY	IRRITATION
	Not Available	Not Available
phenol/ formaldehyde polymer sodium salt	TOXICITY	IRRITATION
	Not Available	Not Available
bifenthrin	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[2] Oral (rat) LD50: 54.5 mg/kg ^[2]	Eye (rabbit): non-irritant * Skin (rabbit): non-irritant *
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

PHENOL/ FORMALDEHYDE POLYMER SODIUM SALT	No significant acute toxicological data identified in literature search.
BIFENTHRIN	<p>For bifenthrin:</p> <p>Acute Toxicity: Bifenthrin is moderately toxic to mammals when ingested. Large doses may cause incoordination, tremor, salivation, vomiting, diarrhea, and irritability to sound and touch . The dose at which half of the test animal die, the LD50, for bifenthrin is about 54 mg/kg in female rats and 70 mg/kg in male rats. The LD50 for rabbits whose skin is exposed to bifenthrin is greater than 2,000 mg/kg . Bifenthrin does not sensitize the skin of guinea pigs . Although it does not cause inflammation or irritation on human skin, it can cause a tingling sensation which lasts about 12 hours. It is virtually non-irritating to rabbit eyes .</p> <p>Chronic Toxicity: No information Available.</p> <p>Reproductive Effects: The dose at which no toxic effect of bifenthrin is observed on the mother (maternal toxicity NOEL) is 1 mg/kg/day for rats and 2.67 mg/kg/day for rabbits. At higher doses, test animals had tremors . The dose at which no toxic effect is observed on development (developmental toxicity NOEL) is 1 mg/kg/day for rats and is greater than 8 mg/kg/day for rabbits.</p> <p>Teratogenic Effects: Bifenthrin does not demonstrate any teratogenic effects at the highest levels tested (100 ppm, approximately 5.5 mg/kg/day) in a two-generational study in rats .</p> <p>Mutagenic Effects: Evidence of mutagenic effects from exposure to bifenthrin are inconclusive. Studies of mouse white blood cells were positive for gene mutation. However, other tests of bifenthrin's mutagenic effects, including the Ames test and studies in live rat bone marrow cells, were negative .</p> <p>Carcinogenic Effects: There was no evidence of cancer in a 2-year study of rats who ate as much as 10 mg/kg/day of bifenthrin. However, an 87 week feeding study of mice with doses of 7, 29, 71, and 86 mg/kg showed a significantly higher, dose related trend of increased tumor incidence in the male urinary bladder. The incidence was significantly increased at 86 mg/kg/day. Also, females had higher incidences of lung cancer than the controls at doses of 7 mg/kg and higher. The EPA has classified bifenthrin as a class C carcinogen, a possible human carcinogen.</p> <p>Organ Toxicity: Pyrethroids are poisons that affect the electrical impulses in nerves, over-stimulating nerve cells causing tremors and eventually causing paralysis.</p> <p>Fate in Humans and Animals: Bifenthrin is absorbed through intact skin when applied topically. It undergoes similar modes of breakdown within animal systems as other pyrethroid insecticides. In mammals, bifenthrin is rapidly broken down and promptly excreted. Rats treated with 4 to 5 mg/kg, excreted 70 % in the urine and 20% in the faeces within 7 days. After 7 days, the remaining bifenthrin was found accumulated in tissues with high fat content such as the skin and fat in males and females and the ovaries of females . Bifenthrin is less toxic to warm-blooded animals, such as mammals, than to cold-blooded animals</p>

CHH H2 S Termite treated LVL & Hyjoist

	NOEL (dogs) 1.5 mg/day/1y * ADI 0.02 mg/kg * Non-teratogenic in rats (< 2 mg/kg/day) and rabbits (8 mg/kg/day)* No skin sensitisation (guinea pigs) *		
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend: **×** – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

CHH H2 S Termite treated LVL & Hyjoist	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available

phenol/ formaldehyde polymer sodium salt	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available

bifenthrin	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.00015mg/L	4
	EC50	48	Crustacea	0.0016mg/L	4
	EC50	96	Algae or other aquatic plants	0.00145mg/L	3
	NOEC	504	Crustacea	0.000004mg/L	4

Legend: *Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data*

Although treated, the solid wood will decay on ground contact.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
bifenthrin	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
bifenthrin	LOW (LogKOW = 8.1524)

Mobility in soil

Ingredient	Mobility
bifenthrin	LOW (KOC = 3228000)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	
	<ul style="list-style-type: none"> ▶ Recycle wherever possible or consult manufacturer for recycling options. ▶ Consult State Land Waste Management Authority for disposal. ▶ Bury residue in an authorised landfill.

CHH H2 S Termite treated LVL & Hyjoist

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

PHENOL/ FORMALDEHYDE POLYMER SODIUM SALT(40798-65-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

BIFENTHRIN(82657-04-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6
Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 7
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	International Air Transport Association (IATA) Dangerous Goods Regulations
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Index	International Maritime Dangerous Goods Requirements (IMDG Code)
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 2	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5	

National Inventory Status

National Inventory	Status
Australia - AICS	No (bifenthrin)
Canada - DSL	No (bifenthrin)
Canada - NDSL	No (bifenthrin; phenol/ formaldehyde polymer sodium salt)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (bifenthrin; phenol/ formaldehyde polymer sodium salt)
Japan - ENCS	No (bifenthrin; phenol/ formaldehyde polymer sodium salt)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	No (bifenthrin; phenol/ formaldehyde polymer sodium salt)
USA - TSCA	No (bifenthrin)
Taiwan - TCSI	Yes
Mexico - INSQ	No (phenol/ formaldehyde polymer sodium salt)
Vietnam - NCI	No (phenol/ formaldehyde polymer sodium salt)
Russia - ARIPS	No (bifenthrin; phenol/ formaldehyde polymer sodium salt)
Thailand - TECI	No (phenol/ formaldehyde polymer sodium salt)
Legend:	Yes = All CAS declared ingredients are on the inventory No = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

CHH H2 S Termite treated LVL & Hyjoist

Revision Date	25/01/2019
Initial Date	15/06/2006

SDS Version Summary

Version	Issue Date	Sections Updated
13.1.1.1	15/08/2018	Name
14.1.1.1	25/01/2019	One-off system update. NOTE: This may or may not change the GHS classification, Supplier Information

Other information

Ingredients with multiple cas numbers

Name	CAS No
bifenthrin	82657-04-3, 92880-79-0

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC—TWA: Permissible Concentration-Time Weighted Average
- PC—STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit.
- IDLH: Immediately Dangerous to Life or Health Concentrations
- OSF: Odour Safety Factor
- NOAEL :No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.